



- Material: SS304
- O-ring: EPDM
- Mechanical Polish
- Standard Perforated Basket
- Individual Vertical Wooden Packing

N5	Drain	2" BSP female with plug	
N4	Gauge	1/2" BSP female with plug	
N3	Vent	1/2" BSP female with plug	
N2	Outlet	SOCKET BSP 2"	
N1	Inlet	SOCKET BSP 2"	
Nozzle	descreption	Nom.Size	facing

7	PIN 16*54	SS304	PIN-A-16*54
6	PIN 16*71	SS304	PIN-A-16*71
5	Eye bolt M16*65	SS304	EB-A-M16*65
4	O-ring	EPDM	OR-SF-E-C01
3	Fixing ring	SS304	BFR-SF-182-A
2	Basket 02# ID.171mm	SS304	FBK-02-A-F171
1	Leg	SS304	LAY-195
ITEM	DESCRIPTION	MATERIAL	PART NO.

technical data

	vessel	jacket	
design pressure	10		bar
design temperature	120		°C
operating pressure max.	10		bar
operating temperature max.	100		°C
test pressure with water 20°C			bar
volume	27.0		l

S E F A R

draw: JASON DONG
 date: 2020-01-20
 appr.

scale:	drawing no.:	SW180827-SF-A-P	
1:1	name:	PV-BS2-304-2B-P	REV. 1